

40312-XXXX**MSDS****MATERIAL SAFETY DATA SHEET**

RUPERT, GIBBON & SPIDER PO BOX 425, HEALDSBURG CA, 95448 TEL: (707) 433-9577 FAX: (707) 433-4906

Jacquard Screen Ink**MSDS No: # N/A****Effective Date: 06/01/06****Amendatory Date: 08/31/06****1. Product Identification**

Product Name: Jacquard Screen Ink
Product Code: N/A

2. Hazardous Ingredients

Ingredients	%	ACGTH-TLV	OSHA-PEL	CAS No.
Formaldehyde	0.12-0.18	1 C ppm	1.0	50-00-0
Residual Monomers	<0.1	NR	NR	N/A

3. Physical Data

Boiling Point: N/A
Vapor Pressure: N/A
Vapor Density: >1
Solubility in Water: N/A
Appearance & Odor: Thick Liquid
Specific Gravity: 1.14-1.45
Melting Point: N/A
Evaporation Rate: N/A

4. Fire and Explosive Data

Flash Point: >200 F
Extinguishing Media: Foam, Co2, Dry Chemical or water mist
Special Fire Fighting Procedures: Wear self-contained breathing apparatus
Unusual Fire or Explosive Hazards: None

5. Reactivity Data

Stability: Stable
Incompatibility (materials to avoid): None
Hazardous Decomposition Products: CO3, CO2
Hazardous Polymerization: Will not occur

6. Health Effects Data

Routes of Entry: N/A
Acute: N/A
Chronic: N/A
Carcinogenic: Formaldehyde and trace amounts of acrylic monomers. Listed hazard values refer only to Formaldehyde in its gaseous form. These liquid paints contact the dissolved form.
Signs & Symptoms of Exposure: Low hazard for industrial use. Any material that contacts the eye may cause a mechanical irritation. Very low toxicity if ingested. Fumes formed at elevated temperatures can be irritating if inhaled.
Medical Conditions Aggravated by Exposure: N/A

7. Emergency and First Aid Procedures

MSDS **MATERIAL SAFETY DATA SHEET**

RUPERT, GIBBON & SPIDER PO BOX 425, HEALDSBURG CA, 95448 TEL: (707) 433-9577 FAX: (707) 433-4906

Eye Contact: Flush with water for at least 15 minutes. If irritation develops, get medical attention.

Skin Contact: Wash with soap and water.

Ingestion: Rinse mouth and then drink plenty of water.

Inhalation: Remove to fresh air for relief.

8. Employee Protection Recommendations

Respiratory Protection: Not necessary at room temperature.

Ventilation: Local exhaust as needed near processing equipment.

Protective Gloves: Usually not required.

Eye Protection: Safety glasses recommended

Other Protection: Usually not required.

Storage & Handling: Do not store near heat or flame. Material can gel with long exposure to elevated temperatures (above 95 F). Wash thoroughly after handling.

9. Spill or Leak Procedures

In Case Material is Released/Spilled: Dike to contain spill. Keep product from entering drains. Recover free product. Collect remaining product with absorbent materials.

Waste Disposal Method: Dispose of materials in accordance with the applicable local, state and federal regulations.

Notice to Reader

The information contained in this MSDS is based on data from sources considered to be reliable but Rupert, Gibbon & Spider Inc. does not guarantee the accuracy or completeness thereof. Rupert, Gibbon & Spider Inc. urges each customer or recipient of this MSDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology or fire and understand the data in this MSDS.