



MATERIAL SAFETY DATA SHEET

SECTION 1 — IDENTIFICATION

Product identifier: AlbaChem® Premium Flash Adhesive
Product Number: 1786
CAS Number: Mixture See Section 2.
Product Family: Aerosol Adhesive
HMIS: Health 2 Flammability 4 Physical Hazard: 1 Personal Protection: B
NFPA Rating as an Aerosol: Level 3

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street
 Long Island City, New York
 United States
 11106
 718-392-6272

5439 San Fernando Road West
 Los Angeles, California
 United States
 90039
 818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300
 (For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This MSDS complies with 29CFR 19190.1200 (Hazard Communication Standard) and WHMIS regulations.

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customer, and users of this product.

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	COMPONENT NAME	CAS NO.	WT/WT % Less Than
01	Hexane	110-54-3	25.0%
02	Dimethyl Ether	115-10-6	15.0%
03	Isobutane	75-28-5	15.0%
04	Cyclohexane	110-82-7	15.0%
05	Acetone	67-64-1	15.0%
06	Ethane, 1,1-Difluoro	75-37-6	10.0%
07	Propane	74-98-6	5.0%

EXPOSURE LIMITS

ITEM	ACGIH		OSHA		COMPANY	
	TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA	SKIN
01	50 ppm	N.E.	500 ppm	N.E.	N.E.	NO
02	N.E.	N.E.	N.E.	N.E.	1000 ppm	NO
03	N.E.	N.E.	N.E.	N.E.	1000 ppm	NO
04	100 ppm	N.E.	300 ppm	N.E.	N.E.	NO
05	500 ppm	750 ppm	1000 ppm	N.E.	N.E.	NO
06	N.E.	N.E.	N.E.	N.E.	1000 ppm	NO
07	2500 ppm	N.E.	1000 ppm	N.E.	N.E.	NO

(See Section 16 for abbreviation legend)

SECTION 3 — HAZARDOUS IDENTIFICATION

***** EMERGENCY OVERVIEW ***:** Keep from reach of children. Do not puncture, incinerate, or place aerosol product containers in compactors. Containers of this material may be hazardous when emptied since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

EFFECTS OF OVEREXPOSURE – EYE CONTACT: Can cause severe irritation, redness, tearing, blurred vision.

EFFECTS OF OVEREXPOSURE – SKIN CONTACT: Prolonged or repeated contact can cause moderate irritation defatting, dermatitis.

EFFECTS OF OVEREXPOSURE – INHALATION: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation. Possible cardiac arrhythmias at high concentrations. Overexposure may cause damage to the nervous system.

EFFECTS OF OVEREXPOSURE – INGESTION: No Information.

EFFECTS OF OVEREXPOSURE – CHRONIC HAZARDS: Overexposure to this material (or its components) has apparently been found to cause the follow effects in laboratory animals: kidney damage, eye damage, liver damage, lung damage, nasal damage, nervous system damage, testis damage.

Overexposure to this material (or its components) has apparently been found to cause the following effects in humans: visual impairment, central nervous system effects.

PRIMARY ROUTE (S) OF ENTRY: SKIN CONTACT SKIN ABSORPTION INHALATION EYE CONTACT

SECTION 4 — FIRST AID MEASURES

FIRST AID – EYE CONTACT: Flush with large amounts of water, lifting upper and lower lids occasionally, get medical attention.

FIRST AID – SKIN CONTACT: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. Get medical attention if irritation persists. Mineral oil, baby oil, make-up remover, mineral spirits, or other similar mild solvent may be used to remove the sticky resin residue left by the adhesive.

FIRST AID – INHALTION: Remove individual to fresh air. If breathing is difficult, administer oxygen. Give artificial respiration if breathing has stopped. Keep person warm and quiet. Get medical attention.

FIRST AID – INGESTION: Do not induce vomiting. Give two glasses of water if conscious. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 5 — FIRE FIGHTING MEASURES

FLASH POINT: -156°F
(PENSKY-MARTENS C.C.)

LOWER EXPLOSIVE LIMIT: 1.0%
UPPER EXPLOSIVE LIMIT: 18.0%

AUTOIGNITION TEMPERATURE: N.D.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors are heavier than air and travel along the ground or may be moved by ventilation and ignited by ignition sources at locations distant from material handling point. For aerosol products – exposure to temperatures over 130°F may cause containers to burst releasing highly flammable gas.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires. Keep fire exposed containers cool with water fog.

SECTION 6 — ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate sources of ignition & ventilate area. Persons not properly equipped should be excluded from area. Stop spill at source – prevent spreading. Avoid inhalation of vapors. Avoid skin contact with liquid. Soak up on absorbent material and place into proper container for disposal. Use non-sparking scoops for flammable materials. Clean walking surfaces thoroughly to reduce slipping hazard.

SECTION 7 — HANDLING AND STORAGE

HANDLING: Containers of this material may be hazardous when emptied, since containers retain product residues (vapour, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch on containers. Intentional misuse by deliberately concentrating and inhaling the vapors from this produce may be harmful or fatal.

STORAGE: Do not store above 120°F. Do not store in direct sunlight. Keep away from heat sources, open flame, pilot lights, sparks, and other sources of ignition. Do not store above 120°F. Do not store in direct sunlight.

SECTION 8 — EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Provide sufficient mechanical ventilation (general and/or local exhaust) ventilation to maintain exposure below TLV (s).

RESPIRATORY PROTECTION: If work place exposure limits of product or any component is exceeded, use a NIOSH/MSHA approved respirator. Consult your safety equipment supplier for recommendations.

SKIN PROTECTION: Wear impervious gloves if method of use involves skin contact with product. Consult your safety supply vendor for glove recommendations.

OTHER PROTECTIVE EQUIPMENT: Wear impervious clothing if bodily exposure is anticipated. Contact your safety supply vendor for recommendations.

HYGIENIC PRACTICES: Wash hands before eating or smoking. Smoke in designated areas only. Remove and launder clothing if contaminated.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: -44 - 177°F	VAPOR DENSITY: Is heavier than air.
ODOR: MINT WHEN WET	ODOR THRESHOLD: N.D.
APPEARANCE: WHITE LIQUID	EVAPORATION RATE: Is faster than Butyl Acetate.
SOLUBILITY IN H ₂ O: NEGLIGIBLE	SPECIFIC GRAVITY: 0.7298
FREEZE POINT: N.D.	pH @ 0.0 %: N.D.
VAPOR PRESSURE: N.D.	VISCOSITY: N.D.
PHYSICAL STATE: LIQUID	COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.

(See Section 16 for abbreviation legend)

SECTION 10 — STABILITY AND REACTIVITY

CONTIONS TO AVOID: Heat, sparks, welding arcs, open flame, pilot lights, static electricity or other source of ignition.

INCOMPATIBILITY: Oxidizing agents, acids, alkali, alkaline earth, metals, reducing agents, strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Hydrofluoric acid and possibly carbonyl fluoride. Carbon monoxide and carbon dioxide, various hydrocarbons, sulphur dioxide, sulphur monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 — TOXICOLOGICAL INFORMATION

No product or component toxicological information is available.

SECTION 12 — ECOLOGICAL INFORMATION

ECOLOGICAL INFOMRATON: No information.

SECTION 13 — DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

SECTION 14 — TRANSPORT INFORMATION

DOT PROPER SHIPPING NAME: Aerosols

DOT TECHNICAL NAME:

DOT HAZARD CLASS: 2.1

HAZARD SUBCLASS: None

DOT UN/NA NUMBER: UN1950

PACKING GROUP: NONE

RESP. GUIDE PAGE: 126

ADDITIONAL INFORMATION: For domestic ground transportation this product may be shipped as a Consumer Commodity ORM-D or as a Limited Quantity. Outer cartons must have the ORM-D designation or Limited Quantity diamond. DOT is transitioning from Consumer Commodity ORM-D marking to the new Limited Quantity diamond, which affords many of the same benefits as Consumer Commodity ORM-D. (our original cartons are currently preprinted with the ORM-D designation for ground shipment, but we are transitioning to the ground version of the Limited Quantity diamond the second quarter of 2012).

SECTION 15 — REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS –

OSHA: Hazardous by definition of Hazard Communication Statndard (29 CFR 1910-1200)

CERCLA – SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA ‘Hazard Categories’ promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD
PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

HEXANE – CAS NUMBER: 110-54-3

WT/WT % IS LESS THAN 25.0%

CYCLOHEXANE – CAS NUMBER: 110-82-7

WT/WT % IS LESS THAN 15.0 %

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States: No information is available.

INTERNATIONAL REGULATIONS: AS FOLLOWS –

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information is available.

TSCA Inventory: All components of this product are on the US TSCA inventory. Hexane is a mixture of n-hexane and other compounds all falling under the general chemical name light hydrotreated distillate CAS-68410-97-9. The n-hexane content of our hexane is 60 to 70 percent. On June 30, 1993 the OSHA Z-1-A table was revoked and OSHA reverted back to their prior exposure limits. The values on this MSDS reflect the roll back to the prior values. Some states may continue to enforce the 1993 limits. On June 16, 1995 EPA announced in a final rule that acetone would no longer be considered a VOC for air attainment standards. (It is now an exempt compound.) The VOC calculation on this MSDS are based on acetone being an exempt compound. The June 16 rule also removed acetone from the list of SARA 313 reportable chemicals.

SECTION 16 — OTHER INFORMATION

HMIS RATINGS: HEALTH: 2, FLAMMABILITY: 4, PHYSICAL HAZARD: 1, PERSONAL PROTECTION: B

VOLATILE BY WEIGHT: 80.9%

VOLATILE BY VOLUME: 86.1%

VOC CONTENT: 63.0% BY WEIGHT, 459 GRAMS/LITER TOTAL PRODUCT,
544 GRAMS/LITER LESS WATER AND EXEMPT, 0.52 LBS/CAN

LEGEND: N.A. – NOT APPLICABLE, N.E. – NOT ESTABLISHED, N.D. – NOT DETERMINED.

Prepared by: Albatross USA Inc.

Telephone number: 718-392-6272

Preparation Date: November 4, 2009

Revision Date: August 7, 2012

NOTICE:

The information in this document is believed to be correct as of the date issued. However, no warranty of merchantability, fitness for any particular purpose, or any other warranty is expressed or to be implied regarding the

accuracy or completeness of this information or the product, the safety of this product, or the hazards related to its use. This information and product are furnished “as is” and on the condition that the personal receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use thereof.